

Aluminum Adjustable Height Gantry Crane with V-Groove Ductile Steel Casters 15 Ft. Wide x 10 Ft. Max Usable Height 4,000 Lb. Capacity Silver

MODEL AHA-4-15-10-VG

Overhead Lifting / Adjustable Height Aluminum Gantry Cranes with V-Groove Casters



PRODUCT OVERVIEW

The adjustable height Aluminum Gantry crane combines lightweight and rigid, sturdy construction into one unit. The all aluminum construction of this gantry crane makes it corrosion resistant and perfect for outdoor use. The lightweight I-beam allows simple height adjustments. All pinned connections make it possible for single person set up and take down in just minutes. Included are two straps, allowing one person to transport the gantry crane in one neat package. Unit comes standard four (4) V-groove casters, allowing for quick movement and positioning adjustments.

KEY FEATURES

- Heavy-duty welded aluminum construction for long lasting use
- Easy adjustable height can be done with fork truck or other overhead lifting device
- Beam length allows for use with items, both large and small
- All units comply with applicable CMAA and ANSI specifications

CORE PRODUCT DATA

ASSEMBLED WEIGHT
343 lbs

ASSEMBLED SIZE
53.9375" W x 180" L x 108.125" H

SHIP WEIGHT
370 lbs

PACKAGE 1 SIZE
29" W x 180" D x 20" H

COLOR / FINISH
Silver

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: YES

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	4,000
Adjustable Clearance Range (in.)	92 to 122
Beam Height (in.)	10
Overall Beam Length (in.)	180
Usable Beam Length (in.)	156-1/4
Flange Width (in.)	4-11/16
Increment Height Adjustment (in.)	6
Caster Qty/Diameter/Width (in.)	(4) 8 x 3
Caster Material	Ductile Steel

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1755>