

# Steel Electric Hydraulic Lift Table 40 In. x 48 In. 3000 Lb. Capacity Blue

**MODEL EHLT-4048-3-43**

Ergonomic Solutions / Electric Hydraulic Scissor Lift Tables

## PRODUCT OVERVIEW

The electric hydraulic scissor lift table is used by all types of manufacturing and warehouse facilities. Safety features include a patented pinch point perimeter toe guard to protect pinch points while lowering the table, fused push button control, internal safety velocity fuse to maintain platform height in the event of hose or fitting failure, integral maintenance prop, adjustable upper travel limit switch to stop the table at maximum height, and displacement-style hydraulic cylinders for maximum strength. It also features a pressure plated pump, manifold system, and state-of-the-art lifetime lubricated bearings. The standard 56 frame electric motor is fully enclosed with additional voltage options available. Contact factory if platform dimensi...

## KEY FEATURES

- Four-sided electric toe-guard meets OSHA pinch point specification
- Durable aluminum pressure-plated hydraulic pump provides maximum efficiency
- Displacement-style hydraulic cylinders offer maximum strength
- Welded steel construction provides reliable heavy-duty use

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**700 lbs**

**ASSEMBLED SIZE**  
**40.375" W x 51" L x 7" H**

**SHIP WEIGHT**  
**807 lbs**

**PACKAGE 1 SIZE**  
**52" W x 52" D x 16" H**

**COLOR / FINISH**  
**Blue**



**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY** Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

**QUICKSHIP: YES**

## ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                  |                 |
|----------------------------------|-----------------|
| Uniform Capacity (lb.)           | 3,000           |
| Travel Time (sec.)               | 16              |
| Vertical Travel (in.)            | 36              |
| Voltage/Phase                    | 460/3           |
| Hertz                            | 60              |
| Motor Horsepower                 | 2               |
| Hydraulic Component Rating (psi) | 3000            |
| Cord Length (in.)                | 96              |
| Push Button Hand Control         | 24V AC          |
| Raised Height (in.)              | 43              |
| Lowered Height (in.)             | 7               |
| Platform Width/Length (in.)      | 40-3/8 x 48-3/8 |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA