

Steel Ground Lift Scissor Table 44 In. x 50 In. 2000 Lb. Capacity Blue

MODEL EHLTG-4450-2-36

Ergonomic Solutions / Ground Lift Scissor Tables



PRODUCT OVERVIEW

The ground lift scissor table is designed for use when fork trucks are not available. The pallets can be loaded onto the platform with pallet trucks and raised to an ergonomic working height. Safety features include an entry-side electric toe guard to protect pinch points during lowering of the table, velocity fuse to maintain platform height in the event of a hose or fitting failure, foot control, maintenance prop, and upper travel limit switch to stop the table at maximum height and reduce motor wear. The motor is totally enclosed standard with additional voltage options available. The remote power unit can be located up to eight (8) feet away from the table. Optional accordion skirting is available.

KEY FEATURES

- Pallets can be loaded onto the platform and raised to a working height
- Features entry-side electric toe guard to protect pinch points
- Includes velocity fuse to maintain platform height
- Remote power unit can be located up to eight feet away from the table

CORE PRODUCT DATA

ASSEMBLED WEIGHT
1455 lbs

ASSEMBLED SIZE
70.875" W x 56.25" L x 8.375" H

SHIP WEIGHT
1573 lbs

PACKAGE 1 SIZE
72" W x 68" D x 21" H

COLOR / FINISH
Blue


FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: --

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	2,000
Platform Width (in.)	44
Platform Length (in.)	51-1/2
Platform Raised Height (in.)	36
Platform Lowered Height (in.)	1/2
Hydraulic Component Rating (psi)	3,000
Motor Horsepower	2
Hertz	60
Voltage	460
Phase	3
Remote Power Unit Length (in.)	32-1/2
Remote Power Unit Width (in.)	12
Remote Power Unit Height (in.)	12-1/2
Lift Time - Up (seconds)	40
Lift Time Down - (seconds)	13

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA