

Steel Electric Pallet Truck with AGM Batteries and Scale 27 In. x 48 In. 4500 Lb. Capacity

MODEL EPT-2748-45-SCL-AGM

Ergonomic Solutions / Electric Pallet Trucks with Scale

PRODUCT OVERVIEW

The electric pallet truck with scale can verify inbound and outbound freight right on your pallet truck and then move your loads with ease. The LCD scale and function keys (zero, tare, net/gross, print, LB/KG), displays weight in 1 pound increments within trucks rated capacity. The scale display operates on standard alkaline batteries (best accuracy is 0.01 percent of maximum calibrated weight). The scale is not NTEP approved (not legal for trade). Scale head includes RS232 port for serial printing. An individual can raise and lower loads with a push of a button. The unit makes it easy to maneuver loads in warehouses and trailers. Reinforced welded forks with adjustable tie-rods provide long service. The high torque DC drive and lift motor handles...

KEY FEATURES

- Fully-powered pallet truck makes movement of pallets quick and easy
- Includes fingertip raise and lower buttons for operator convenience
- Safety belly reverse button improves worker safety
- Easy-to-operate throttle for forward and reverse direction

CORE PRODUCT DATA

ASSEMBLED WEIGHT
1036 lbs

ASSEMBLED SIZE
51.375" W x 76.5" L x 30.1875" H

SHIP WEIGHT
1234 lbs

PACKAGE 1 SIZE
43" W x 90" D x 58" H

COLOR / FINISH
Black & Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	4,500
Fork Width x Length (in.)	7-1/16 x 48
Fork Spacing (in.)	27
Service Range (in.)	3-3/8 to 8
Battery Qty./Type	(4) 6V FLA (Flooded Lead Acid)
DC Motor Voltage	24
Battery Charger	120V Input, 24V/20 amp
Drive KW	1.2
Lift Motor KW	2.0
Turn Radius (in.)	69
Operation Time with Full Charge	6 to 7 hours
Operation Time with Intermittent Use	8 hours
Drive Wheel Diameter/Width (in.)	10 x 3-1/8
Load Roller Diameter/Width (in.)	2-3/4 x 3
Scale Accuracy	0.1% of Applied Load
Battery Depth	10
Battery Width	28
Battery Height	9
Battery Weight	120
Battery Freight Class	60
Battery NMFC Number	60700
Battery NMFC Description	Gel batteries on unit
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA