Steel Portable DC Powered Hefti-Lift 37 In. x 69 In. 880 Lb. Capacity Silver / Black

MODEL HYD-10-DC

Ergonomic Solutions / DC Powered Hefti-Lifts

PRODUCT OVERVIEW

The Hefti-Lift is a user friendly, portable hydraulic lift. The lift provides reliable, power lifting when moving and positioning loads. It includes a removable platform for operation requiring forks. The non-slip chain is used for accurate positioning while the lift rolls easily on two rigid and two swivel poly-on-steel casters that includes a foot operated brake. The unit has an all welded construction with a chrome platform and uprights. Not for use with pallets.

KEY FEATURES

- Non-slip chain provides accurate deck positioning
- Two rigid and two swivel poly-on-steel casters roll smoothly either loaded or unloaded
- Removable platform allows operation requiring forks
- Welded steel construction provides long lasting rugged use

CORE PRODUCT DATA

ASSEMBLED WEIGHT **269 lbs**	ASSEMBLED SIZE **23" W x 36" L x 70" H**	SHIP WEIGHT **348 lbs**
PACKAGE 1 SIZE **41" W x 65" D x 74" H**	COLOR / FINISH **Silver / Black**	FREIGHT TYPE **LTL Palletized**

AVAILABILITY Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	880
Platform Width/Length (in.)	23 x 24
Service Range (in.)	3-1/2 to 59
Operation	(1) 12V DC
Fork Width/Length (in.)	4-3/8 x 24
Fork Spacing (in.)	21-3/4
Handle Height (in.)	42
Back Caster Qty./Diameter/Width (in.)	(2) 5 x 2
Back Caster Type	Swivel with Brake
Front Caster Qty./Diameter/Width (in.)	(2) 3 x 1-1/2
Front Caster Type	Rigid
Caster Material	Poly-on-Steel
Outrigger Inside Dimension (in.)	14
Outrigger Outside Dimension (in.)	18-1/4
Battery Depth	11
Battery Width	7
Battery Height	9
Battery Weight	42
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **90 Days**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?FID=262