

Steel Lite Load Lift With Winch, Swivel Casters and Manual Floor Lock 24 In. x 20 In. Platform 400 Lb. Capacity Blue

MODEL LLW-242060-4SFL

Ergonomic Solutions / Lite Load Lifts

PRODUCT OVERVIEW

The Lite load lift is ideal for lifting and transporting loads from delivery trucks to docks, or use to inventory storage systems. This lift has an easy to operate hand winch and an steel construction. The unit rolls smoothly on poly-on-poly rear wheels, four swivel front casters and a hand operated floor lock. Located on the handle are two (2) rollers to ease loading into delivery trucks.

KEY FEATURES

- Solid steel construction provides long lasting rugged use
- Easy to operate lift system makes lifting products to ergonomic heights simple
- Two rear and four swivel front wheel design conveniently rolls when loaded
- Two rollers on handle provide easy unit loading into delivery trucks

CORE PRODUCT DATA

ASSEMBLED WEIGHT
192 lbs

ASSEMBLED SIZE
27.1875" W x 33.125" L x 69.4375" H

SHIP WEIGHT
198 lbs

PACKAGE 1 SIZE
40" W x 48" D x 72" H

COLOR / FINISH
Blue

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	400
Platform Width (in.)	24
Platform Length (in.)	20
Lowered Height (in.)	6-1/8
Raised Height (in.)	60
Per Winch Rotation (in.)	1
Horizontal Load Center (in.)	10
Operation Type	Hand Winch
Rear Wheel Quantity/Diameter/Width (in.)	(2) 8 x 2
Rear Wheel Material	Poly on Poly
Rear Wheel Type	Rigid
Front Caster Quantity/Diameter/Width (in.)	(4) 4 x2
Front Caster Material	Mold on Rubber
Front Caster Type	Swivel
Handle Caster Quantity/Diameter/Width (in.)	(2) 4 x 1-1/4
Handle Caster Material	Poly on Poly
Handle Caster Type	Rigid

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=263>