

Steel Hydraulic Telescoping Boom 12 Volt DC 24 In. Fork Pocket Center 8,000 Lb. Capacity

MODEL LM-1T-8-24-HBE-DC

Fork Truck Attachments / Hydraulic Powered Fork Truck Booms

PRODUCT OVERVIEW

The DC powered telescoping boom has all the benefits of the standard lifting boom, except now it has the capability of being powered. The DC powered design includes a power unit housed between the fork tubes and the outer boom. By using the handheld controller the boom can be extended or retracted. The hand held controller connects to the power unit via a pigtail cord. Painted for a smooth finish and to limit abrasion. Includes two (2) lifting hooks.

KEY FEATURES

- Unique design converts fork trucks into overhead lifting cranes
- Fork pockets with safety strap attach & secure boom to fork truck
- Robotically welded construction provides precision and durability
- Promotes workplace efficiency

CORE PRODUCT DATA

ASSEMBLED WEIGHT
805 lbs

ASSEMBLED SIZE
32" W x 83.75" L x 24.5" H

SHIP WEIGHT
810 lbs

PACKAGE 1 SIZE
34" W x 86" D x 26" H

COLOR / FINISH
Blue (Base Frame)/Yellow (Extension)

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Maximum Movable Load (lbs.)	2,000
Lost Load (lbs.)	815
Extended Length (in.)	144-3/4
Min/Max Hook Point (in.)	36 - 142
Power	12V DC
Usable Fork Pockets (in.)	7-1/4 x 2-1/4
Fork Pocket Center (in.)	24
Fork Truck Required Rating (lbs.)	8000
Max Single Hook Capacity at 36" (lbs.)	8000
Max Single Hook Capacity at 60" (lbs.)	6000
Max Single Hook Capacity at 84" (lbs.)	4650
Max Single Hook Capacity at 108" (lbs.)	3500
Max Single Hook Capacity at 142" (lbs.)	2200
Retracted Center of Gravity (in.)	32-1/4
Extended Center of Gravity (in.)	47-1/2
Battery Depth	8
Battery Width	12
Battery Height	7
Battery Weight	48
Battery Freight Class	60
Battery NMFC Number	60700
Battery NMFC Description	Gel batteries on unit
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1776>