

# Polyphenylene Sulfide Manual Rotary Drum Pump 10 In. 8 In. x 12 In. Black

**MODEL RP-90RT**

Drum Handling Equipment / Rotary Drum Pumps



## PRODUCT OVERVIEW

The manual drum pump is designed for dispensing and transferring liquids out of fifty-five (55) gallon drum. It is ideal for transferring soluble, corrosive, volatile and aggressive chemicals. Suitable for use with acetone and ad-blue.

## KEY FEATURES

- Designed for dispensing liquids out of fifty-five (55) gallon drum
- Outlet spout is made from 304 stainless steel
- Ideal for transferring soluble, corrosive, volatile and aggressive chemicals
- Suitable for use with acetone and ad-blue

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
5 lbs

**ASSEMBLED SIZE**  
8" W x 10" L x 12" H

**SHIP WEIGHT**  
6 lbs

**PACKAGE 1 SIZE**  
7" W x 25" D x 7" H

**COLOR / FINISH**  
Black


**FREIGHT TYPE**  
Parcel

**AVAILABILITY** Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                                |                                                                                                                        |
|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Pump Type                                      | Rotary - Vane                                                                                                          |
| Flow Dispense Per Stroke (ml)                  | 300                                                                                                                    |
| Maximum Fluid Temperature Degrees (Fahrenheit) | 140 Degrees Fahrenheit / 60 Degrees Celsius                                                                            |
| MNPT Bung Size (in.)                           | 2                                                                                                                      |
| Suction Tube Length Maximum (in.)              | 42                                                                                                                     |
| Inlet Outside Diameter (in.)                   | 1-1/4                                                                                                                  |
| Outlet Curved Spot Outside Diameter (in.)      | 1                                                                                                                      |
| Maximum Viscosity (SSU)                        | 2000                                                                                                                   |
| Seal Construction                              | PTFE                                                                                                                   |
| Vane Construction                              | PTFE                                                                                                                   |
| Suction Tube Construction                      | PPS (Polyphenylene sulfide)                                                                                            |
| Adjustable Outlet Degrees                      | 0 - 360                                                                                                                |
| Application Liquids                            | acid, alkali, gasoline, diesel, machine oil, water, alcohol, thinner, Acetone, Ad-Blue, MEK and other chemical liquids |
| Component Materials                            | PPS, PTFE                                                                                                              |
| Nitric Acid Resistance Percentage              | 40                                                                                                                     |
| Displacement per Stroke (ounces)               | 10.14                                                                                                                  |
| Pump Motor Type                                | Crank                                                                                                                  |
| Pump Mounting                                  | Bung                                                                                                                   |
| Self-Priming                                   | Yes                                                                                                                    |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA