

# Steel Rough Terrain Electric Pallet Truck DC Powered AC Drive Motor 48 In. Inside Width 2000 Lb. Capacity Black / Yellow

**MODEL RT-EPT-2-48**

Ergonomic Solutions / Electric Powered Rough Terrain Pallet Trucks

## PRODUCT OVERVIEW

An all-terrain pallet truck is the perfect outfit for moving heavy loads over a variety of landscapes. The simple functionality of the unit allows the user to maneuver the truck, both loaded and loaded, easily. Driving handle is centrally located with functions both on and underneath the handle, located directly on the front console. Functions include an easy to operate throttle with infinite adjustment of forward/reverse speeds, lift/lower controls, emergency reverse-function and horn. Emergency reverse belly switch instantly reverses direction and moves the unit forward (away from the operator). Forks are adjustable to best fit the users needs.

## KEY FEATURES

- Great for indoor or outdoor use
- Large wheels allow use on a variety of surfaces
- Emergency reverse belly switch instantly reverses direction
- Simple lifting and lowering operation

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**1127 lbs**

**ASSEMBLED SIZE**  
**63.5" W x 68.875" L x 48.625" H**

**SHIP WEIGHT**  
**1188 lbs**

**PACKAGE 1 SIZE**  
**65" W x 78" D x 55" H**

**COLOR / FINISH**  
**Yellow/Black**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| Uniform Capacity (lb.)              | 2,000                                 |
| Overall Width (in.)                 | 63-1/2                                |
| Overall Length (in.)                | 68-7/8                                |
| Overall Height (in.)                | 48-5/8                                |
| Fork Length (in.)                   | 42-1/8                                |
| Fork Width (in.)                    | 4                                     |
| Adjustable Fork Spacing Width (in.) | 8-1/2 to 33                           |
| Control                             | Throttle Head                         |
| Drive Motor                         | AC16 / 0.75 KW                        |
| Lift Motor                          | 24V / 0.8 KW                          |
| Lift Speed                          | 1/2" per second                       |
| Service Range (in.)                 | 2-1/8 to 12-3/4                       |
| Battery                             | (2) 12V / 85-95 Ah                    |
| Charger                             | 24V / 12 amp                          |
| Hydraulic Fluid (qt.)               | 2                                     |
| Wheel Material                      | Rubber                                |
| Front Wheel Diameter & Width (in.)  | 14-3/4 x 4-1/2                        |
| Rear Wheel Diameter & Width (in.)   | 11-13/16 x 4                          |
| Travel Speed w/o Load               | 2.3 mph                               |
| Travel Speed w/ Load                | 1.8 mph                               |
| Battery Depth                       | 11                                    |
| Battery Width                       | 7                                     |
| Battery Height                      | 9                                     |
| Battery Weight                      | 78                                    |
| Battery Freight Class               | 70                                    |
| Battery NMFC Number                 | 60680                                 |
| Battery NMFC Description            | UN2794 BATTERIES WET FILLED WITH ACID |
| Battery Subclass                    | 1                                     |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?EID=1451>