

Steel Adjustable Spreader Beam 104-1/2 In Length 8,000 Lb. Capacity Blue

MODEL SBM-80

Overhead Lifting / Adjustable Spreader Beams

PRODUCT OVERVIEW

The adjustable spreader beam is ideal for the manufacturing and maintenance facilities. The steel construction keeps the unit durable and strong for a lifetime of use. The beam is shipped with a test certificate.

KEY FEATURES

- Designed to lift and move uneven and awkward loads
- Complies with ASME B30.20-1993 standards
- Includes two lower bails and one upper bail standard for added versatility
- Welded steel construction for heavy duty performance



CORE PRODUCT DATA

ASSEMBLED WEIGHT
265 lbs

ASSEMBLED SIZE
6" W x 104.5" L x 24.5" H

SHIP WEIGHT
336 lbs

PACKAGE 1 SIZE
34" W x 107" D x 12" H

COLOR / FINISH
Blue



FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: YES

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	8,000
Headroom (in.)	20-3/4
Minimum Spread (in.)	8
Maximum Spread (ft.)	8
Usable Upper Bail Width/Height (in)	4 x 6-3/4
Usable Lower Bail Width/Height (in.)	3 x 5-1/4
Upper/Lower Bail Thickness (in.)	1-1/4; 1
ASME	B30.20-1993
C-Channel Height (in.)	8
Overall Height (in.)	24-1/2
Overall Width (in.)	6
Overall Length (in.)	104-1/2

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA