

Steel Narrow Mast Stacker DC Powered 62 In. Raised Height Fixed Fork 21 In. Fork Width 2,200 Lb. Capacity Black / Yellow

MODEL SNM-62-FF-21

Ergonomic Solutions / Narrow Mast Stackers with Powered Drive and Powered Lift

PRODUCT OVERVIEW

The narrow mast stacker is great for the shipping and manufacturing facilities. The stacker provides a fast efficient solution to loading and unloading products in closely confined areas. The stacker features a simple throttle design for lifting control, as well as, infinite forward and reverse speed adjustments. The unit drives on poly on steel steering and load wheels, which provide excellent maneuverability. A battery charger, gauge and horn are included. Models are available with fixed or adjustable forks as well as fixed or adjustable leg supports.

KEY FEATURES

- Emergency reverse belly switch instantly reverses direction
- Stacker is an efficient solution to loading and unloading in closely confined areas
- Throttle design lifts and controls speed adjustments for ideal operation and optimal results
- Includes poly-on-steel wheels for excellent maneuverability and fixed forks for maximum efficiency

CORE PRODUCT DATA

ASSEMBLED WEIGHT
932 lbs
ASSEMBLED SIZE
32" W x 68.5" L x 78.5" H
SHIP WEIGHT
899 lbs
PACKAGE 1 SIZE
60" W x 75" D x 84" H
COLOR / FINISH
Black / Yellow
FREIGHT TYPE
LTL Palletized
AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: --

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	2,200
Service Range (in.)	2-3/8 to 62
Fork Width/Length (in.)	5-9/10 x 42-1/8
Fixed Fork Spacing (in.)	20-1/2
Overall Mast Height (in.)	78-3/4
Drive Motor (in.)	DC 24V / 1.0 KW
Lift Motor (in.)	DC 24V / 2.0 KW
Battery	(2) 12V / 80-95 Ah
Battery Charger	24V / 12 amp
Operation Time with Constant Use (hrs.)	3-4
Operation Time with Intermittent Use (hrs.)	8
Travel Speed - Loaded (MPH)	2.8
Travel Speed - Unloaded (MPH)	3.4
Battery Depth	11
Battery Width	14
Battery Height	9
Battery Weight	84
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA