

# Steel AC Powered Jib Crane CSA Compliant 3-1/2 to 5-1/2 Ft. Boom 1,500 Lb. Capacity Blue

**MODEL WTJ-E-15-3-AC-CSA**

Overhead Lifting / Power Lift Jib Cranes

## PRODUCT OVERVIEW

A power lift Jib crane is designed for material handling applications on docks, in warehouses or in truck beds. This lift jib crane is the economical answer to your material handling problems. It offers light-duty, intermittent use. Locking manual rotation. The cable has a swivel snatch block and safety latch. Unit is designed for vertical lifting only. Do not use unit for lifting personnel or overhead lifting.

## KEY FEATURES

- Powered cable winch makes lifting and maneuvering easy
- Boom telescopes in and out for greater reach and versatility
- 360 Degrees swivel design allows for maximum accessibility
- Pre-drilled base plate makes mounting quick and easy

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**176 lbs**

**ASSEMBLED SIZE**  
**18.6875" W x 66.75" L x 67.5" H**

**SHIP WEIGHT**  
**227 lbs**

**PACKAGE 1 SIZE**  
**29" W x 66" D x 17" H**

**COLOR / FINISH**  
**Blue**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                             |                   |
|---------------------------------------------|-------------------|
| Uniform Capacity (lb.)                      | 1,500             |
| Boom Reach (in.)                            | 43-1/16 to 66-3/4 |
| Boom Height (in.)                           | 47-1/8 to 73-5/16 |
| Rotation Degree                             | 360               |
| Boom Adjustment Increments (in.)            | 12                |
| Cable Length (ft.)                          | 25                |
| Cable Diameter (in.)                        | 7/32              |
| AC (volts)                                  | 115               |
| Horsepower (HP)                             | 1/3               |
| Mounting Plate Length (in.)                 | 12                |
| Mounting Plate Width (in.)                  | 12                |
| 1,500 lb. Capacity at Boom Extension (in.)  | 27-13/16          |
| Capacity at 47-1/8" Fully Retracted (lbs.)  | 650               |
| Capacity at 47-1/8" Mid-Position (lbs.)     | 300               |
| Capacity at 47-1/8" Fully Extended (lbs.)   | 200               |
| Capacity at 56-3/16" Fully Retracted (lbs.) | 1100              |
| Capacity at 56-3/16" Mid-Position (lbs.)    | 650               |
| Capacity at 56-3/16" Fully Extended (lbs.)  | 550               |
| Capacity at 64-3/4" Fully Retracted (lbs.)  | 1,250             |
| Capacity at 64-3/4" Mid-Position (lbs.)     | 850               |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=582>